

**Class I, Div. 1 & 2, Groups C,D
Class II, Div. 1 & 2, Groups E,F,G
Class III**

-  Listed - File E10514
-  Certified - File LR11716
-  File 25215
- APPROVED See files for details or call Killark.

FEATURES-SPECIFICATIONS

KDB/KB

Applications

- When installed in the top of an enclosure, these fittings act as breathers
- Bottom installations permit water to drain from the enclosure continuously
- All drains and breathers are designed for use in 1/2" hubs or 1/2" drilled and tapped conduit openings
- KDB-1 can be used as a drain or breather

Features

- Tapered threads (NPT)

Material/Finish

Stainless Steel

DRAINS AND BREATHERS		
CATALOG NUMBER	DESCRIPTION	SUITABILITIES
KDB-1 ①③	Drain or Breather	CLASS I Div. 1 & 2, Groups C, D CLASS II Div. 1 & 2, Groups E, F, G CLASS III
KB1B ①③	Breather (Group B)	CLASS I Div. 1 & 2, Groups B, C, D CLASS II Div. 1 & 2, Groups E, F, G CLASS III
KB1D ②③	Drain (Group B)	CLASS I Div. 1 & 2, Groups B, C, D CLASS II Div. 1 & 2, Groups E, F, G CLASS III

- ① UL Listed and CSA Certified
- ② UL Listed only
- ③ FM Approved

KSBF

Applications

- When installed in the top of an enclosure, these fittings act as breathers
- Bottom installations permit water to drain from the enclosure continuously
- KSBF breathers and drains are designed for punched M25 entries in standard location or Ex e sheet metal or non-metallic enclosures

Features

- M25 x 1.5 metric threads
- Includes notched locknut



Material/Finish

- Polyamide
- Green in color



KSBF

**EEx e II
Ex e II**

-  PTB Ex-95.D.3148U
-  Call for details

NON-METALLIC DRAINS AND BREATHERS— EEx e II, IP54 RATED	
CATALOG NUMBER (INCLUDES LOCKNUT)	THREAD SIZE
KSBF-M25	M25 x 1.5